

For simple, clean and effective lighting, the BETA series represents excellent value for

money. With a 3-year warranty for peace mind, BETA is the first choice for any High Bay replacement program. IPART approved also means that they qualify for Govt energy rebates. Using only high quality componetry, BETA is hard to beat!



SPECIFICATIONS SPECIFICATIONS			
PART NUMBERS	Beta6 100W	Beta6 150W	Beta6 200W
	TECHNICAL	PARAMETER	
VOLTAGE	AC85V-265V~50./60Hz		
POWER	100W	150W	200W
LUMEN (±10%)	15000lm	22500lm	30000lm
LED TYPE	SMD 2835		
COLOR TEMPERATURE (CCT)	2700K-6500K		
BEAM ANGLE	60°/90°/120°		
COLOR RENDERING INDEX (CRI)	Ra > 80		
POWER SUPPLY EFFICIENCY	>95%		
LUMINOUS EFFICIENCY	150lm/W		
POWER FACTOR	>0.95		
IP RATING	IP65		
CERTIFICATE	C-TICK, SAA, CE, CB		
MATERIAL	AL + Tempered Glass		
G.W	2.4kg	3.2kg	3.8kg
DIMENSION	ф260 x (H) 164 mm	ф305 x (H) 171 mm	ф343 x (H) 178 mm
TEMPERATURE RANGE OPERATING	-40°C to 50°C		
OPTIONAL CONTROL MODULES	 Motion and daylight sensor Detection area: 6-12m Dimming function: 20% / 50% 	Dimming time: 30s/60s/90s/120s/30mins.With remote control	